

# (12) UK Patent Application (19) GB (11) 2 270 000 (13) A

(43) Date of A Publication 02.03.1994

(21) Application No 9317635.2

(22) Date of Filing 25.08.1993

(30) Priority Data

(31) PL4299

(32) 26.08.1992

(33) AU

(71) Applicant(s)

Robert John Grace  
44 Kintore Avenue, Prospect, South Australia,  
Australia

Avenel Faye Grace  
44 Kintore Avenue, Prospect, South Australia,  
Australia

(72) Inventor(s)

Robert John Grace  
Avenel Faye Grace

(74) Agent and/or Address for Service

Edward Evans & Co  
Chancery House, 53-64 Chancery Lane, LONDON,  
WC2A 1SD, United Kingdom

(51) INT CL<sup>5</sup>

A61N 2/04

(52) UK CL (Edition M )

A5R RHFMX

(56) Documents Cited

GB 2156679 A	GB 2143131 A	GB 1466337 A
EP 0459402 A2	EP 0048451 A1	WO 91/06341 A1
WO 89/05673 A1	US 5085626 A	US 4993413 A

(58) Field of Search


UK CL (Edition L ) A5R RHFMX RHXT

INT CL<sup>5</sup> A61N 2/02 2/04

Online database : WPI

(54) Magnetic field induction multi - pulse therapy.

(57) Apparatus for therapeutic treatment includes a circuit 6-10 for converting an AC input supply into a multi-rhythmic pulsed alternating signal in the frequency range 0.5 to 25 Hz. The signal is coupled to a coil or coils for applying magnetic fields to a human, equine or canine body. A controlling microprocessor 1 has control and mode lines 2, 3, a reset 4, timer/buzzer 5 and LCD display output 11. The signal may include higher harmonics to approximate natural body waveforms.



GB 2 270 000 A

At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.

This print takes account of replacement documents submitted after the date of filing to enable the application to comply with the formal requirements of the Patents Rules 1990.




FIG 1




FIG 2

VOLTAGE (AMPLITUDE)




FIG 3





FIG 4



*FIG 5*

**MAGNETIC FIELD INDUCTION MULTI-PULSE THERAPY**

This invention relates to an improved Magnetic Field Induction Therapy device and an improved method of treatment using Magnetic Field Induction Therapy. The method and device utilise pulsed alternating magnetic fields of specific characteristics  
5 which have been found to be therapeutic.

**BACKGROUND ART**

The therapeutic value of magnetic fields has been known for more than two thousand years. Permanent magnets placed on or adjacent an animal or human body have been used for pain relief and blood circulation improvement. It is also known to use  
10 pulsating magnetic fields for medical and therapeutic purposes.

For over 50 years the use of electro-magnetic fields has been known to be more beneficial than static or permanent magnetic fields. The most common devices use a generator unit to produce a pulsing or time-varying electric current which is fed into a wire-wound coil or coils to produce an electromagnetic field.

15 In most commercially available prior art devices direct current (D.C.) pulses are used to energise the applicator coils. These prior art devices have proven effective in providing temporary pain relief and promoting repair of damaged tissue. The inventors have found that an enhanced effect can be obtained by applying multi-rhythm bio-waveforms of pulsed alternating magnetic fields.

20 Medical science and clinical testing (using an electro-encephalogram) have established that the predominant brain wave activity is a spiked alternating waveform at a frequency of between 8Hz and 13Hz. This is known as the 'alpha' rhythm. Other rhythms detected by an EEG are the 'beta' rhythm at frequencies above 13Hz, the 'theta' rhythm at frequencies between 4Hz and 7Hz and the 'delta' rhythm at  
25 frequencies below 4Hz. Other less common rhythms ('mu' - 9Hz, 'lambda' - 4-6Hz) have also been measured.

It has also been established that the terrestrial magnetic field has a predominant pulsing of 9.6Hz with Schumann Resonance frequencies of 7.83Hz to 7.96Hz. The terrestrial magnetic field and other naturally occurring fields have an induced electrical effect on all living matter at the cellular level. This effect is due to the  
 5 paramagnetic nature of materials in living matter such as DNA and blood. Blood contains iron which is paramagnetic and therefore affected by magnetic fields and the DNA in every cell has positive and negative regions. The basis of magnetic therapy is that artificially produced fields can have a beneficial effect on living tissue by interaction with the paramagnetic components.

10 Electrical potential has been measured across cell walls. This potential is maintained by the movement of ions and in particular,  $\text{Na}^+$ ,  $\text{K}^+$ ,  $\text{Cl}^-$ , and  $\text{HCO}^-$ . Normal cell potentials vary from -60mV in some muscles to as much as -120mV in myocardial cells. This movement of ions is known to have a profound influence on the inflammatory process of living tissue. Cell wall potential differences tend to attract  
 15 positive ions into and negative ions out of the cell, resulting in a reduction in cell potential, an increase in fluid (oedema) and a triggering, under certain conditions, of pain mechanisms. A pulsed alternating magnetic field can influence the net ion flux through the cell membrane to restore the normal cell potential and  $\text{Na}^+$  and  $\text{K}^+$  balance, and release encephalin, endorphin and other chemicals to inhibit or modify  
 20 pain signal transmission.

### **OBJECT OF THE INVENTION**

It is an object of the present invention to provide a method and apparatus which provide therapeutic effects by the use of extremely low frequency, pulsed alternating magnetic fields applied to living tissue.

### **25 DISCLOSURE OF THE INVENTION**

In one form of the invention there is provided an apparatus for therapeutic treatment comprising: a generator unit adapted to provide alternating current;  
 a control means in electrical connection with said generator unit and adapted to receive as input alternating current from the generator unit and to provide electrical  
 30 signals as output; said electrical signals being multi-rhythmic pulsed alternating signals at a frequency in the range of 0.5Hz to 25Hz; and one or more applicator coils in

electrical connection with said control means and adapted to convert the electrical signals to magnetic fields.

In a further form of the invention there is proposed a method of therapeutic treatment including the steps of: locating one or more applicator coils adjacent an area to be  
5 treated; applying electrical signals having frequency, amplitude and pulse characteristics to said applicator coils so as to produce multi-rhythmic, pulsed, alternating magnetic fields in the vicinity of the coils; and adjusting the frequency, amplitude and pulse characteristics so as to produce a pulsating magnetic field having therapeutic effect in the said area to be treated.

## **10 BRIEF DESCRIPTION OF DRAWINGS**

To further assist in understanding the invention reference will be made to the following drawings in which:

Fig. 1 shows a schematic of one preferred embodiment of a control means for the invention;

15 Fig. 2 shows a sketch of a preferred form of applicator coil;

Fig. 3 shows typical EEG waveforms of a human brain;

Fig. 4 shows a frequency analysis of brain waves during different levels of activity;

Fig. 5 shows a typical waveform of the present invention.

## **DETAILED DESCRIPTION OF DRAWINGS**

20 Referring now to the drawings in detail there is shown in Fig. 1 a block diagram of the control means of one preferred embodiment of a magnetic field induction multi-pulse therapy device. The control means includes a microprocessor 1 which controls the characteristics of signals applied to the applicator coils. In the embodiment shown the microprocessor is a 68HC705C8F microprocessor which operates from a 5  
25 volt supply (Vcc), other similar devices may also be used. A number of control lines 2 allow the user to select between a range of values for some of the magnetic field parameters. For example the control lines allow the setting of the duration of treatment and the primary frequency of the applied magnetic field. One control line is a start/stop switch.

In the preferred embodiment the duration of treatment may be selected as 10, 15, 20, 25 or 30 minutes and the frequencies may be chosen as 0.5, 1, 2, 3, 4, 5, 8, 10, 12, 15 or 18Hz. The frequencies are chosen for their beneficial effect and it will be noted that certain frequencies known to have negative effects (such as 13Hz which is known to cause disorientation and to induce epileptic fits) have been omitted. A further setting gives an automatic programme of 30sec at 2Hz, 60sec at 4Hz, 90sec at 8Hz and 120sec at 12Hz repeated four times for a total treatment time of 20 minutes. Another automatic setting is incorporated which continuously repeats intervals of a chosen treatment until manually stopped. For example, if a treatment of 20 minutes at 0.5Hz is chosen this treatment will be applied followed by a 20 minute pause followed by the same treatment and so on until stopped.

At power up the device automatically resets to a default setting of 0.5Hz for 20 minutes otherwise when a treatment is completed the device resets ready to repeat the last treatment.

The inventors have found that this specific sequence of ascending pulse frequencies provides even greater benefits than available from single frequency treatments, particularly in a reduction in the time needed to obtain relief and/or healing.

The use of a microprocessor based control means allows for configuration of the device for a number of different applications. The mode lines 3 can be enabled using wire patches to configure the Magnetic Field Induction Therapy device for human, equine or canine use. The mode lines can also be used to disable some features such as the reset controller 4 or the timer buzzer 5. The reset controller 4 resets the microprocessor to the default settings after a treatment has been completed. The timer buzzer 5 gives an audible indication that a period of treatment has ended.

The control means also includes a triac 6 which is coupled to the microprocessor 1 by opto-coupler 7. An AC signal of 18 volts peak-to-peak at line frequency (ie. 50Hz or 60Hz) is provided at input 8. The signals from the microprocessor 1 control the operation of the triac 6 to provide the desired pulsed AC signal at output 9. The



input AC signal is unfiltered and therefore contains higher harmonics. The arrangement of capacitors and resistors associated with the triac are chosen to allow some higher harmonics to appear at the output 9. As described below this results in an output electrical signal more closely approximating the natural electrical activity of a body. The connections 9 and 10 connect to the applicator coil connections 12 and 13 shown in Fig. 2.

The 18 volt AC signal is provided from a generator unit which is a step-down transformer wound to provide secondary alternating current voltage sources of 18 volts and 7 volts from a primary alternating current voltage source such as a 240 volt or 120 volt household supply. The 7 volt signal is rectified and powers a 5 volt regulator which provides the Vcc source. Although 18 volts AC is used in this embodiment it will be appreciated that other voltages will also be appropriate depending on the specific electrical characteristics of the applicator coils. In an alternate embodiment the voltage is selectable through the control lines 2.

The device is provided with a five volt liquid crystal display which is driven by display lines 11. The LCD indicates the treatment time remaining and the frequency of treatment. Other indications, such as the operation mode or program details can be shown if desired.

A typical applicator coil is shown in Fig. 2. The coil is a pad type having an outside diameter of 170mm and approximately 800 turns of copper wire with an impedance of preferably 15 Ohms. A circular or oval design is chosen to avoid undesirable eddy currents in the magnetic field. Such coils may be covered with a suitable thermal insulating material, cushion layers of a foam plastic and enclosed in a vinyl or other suitable covering envelope.

Other versions may be in the shape of cylindrical tube applicators with layers of coil winding around the circumference. Further versions may have a number of coils connected electrically in series, parallel or a combination of configurations and enclosed in a mat, pad or mattress. The inventors have found that such multiple coil

arrangements should have each coil wound in the same direction, be arranged symmetrically, be of similar dimensions and equal electrical resistance, and be individually insulated to minimise interference fields and eddy currents which are of a non-beneficial nature.

- 5 Specifically shaped coils have been found to produce concentrated projection of the magnetic field which has benefits in specific applications such as dental analgesic. In each case the electrical characteristics of the coil must suit pulsed alternating current provided from the control means.

In a second preferred embodiment a version of the device which can operate from a  
 10 direct current low voltage power source is provided. This device is designed for use in an automobile, truck or bus and can be plugged into the cigarette lighter of a car. Instead of a step-down transformer to convert a household power supply to 18 volts a step-up transformer is used to step-up the DC voltage and a known DC to AC inverter circuit is used to produce the AC source. The Vcc supply is derived directly  
 15 from the DC source. The inverted voltage is pulsed at a frequency of either 50Hz or 60Hz. Harmonic characteristics are added to be similar to that obtained from the AC version described in detail above.

The second embodiment can be particularly useful for relieving muscle cramp and fatigue in long distance drivers. Packets or bursts of pulses at a rhythmic rate with  
 20 frequencies between 10Hz and 20Hz have been found useful for this purpose without causing sleepiness or lack of concentration.

Fig. 3 shows examples of three forms of measured brain waves with amplitude on the vertical axes and time on the horizontal axes. Fig. 3a shows 'delta' waves at below 4Hz typical of some stages of sleep; Fig. 3b shows 'beta' waves at a frequency above  
 25 13Hz typical of an awake and alert state; Fig. 3c shows 'alpha' waves at between 8Hz and 13Hz typical of an awake but relaxed state. It is clear from these traces that the primary electrical activity of the brain (and the rest of the body) is not a clean sinusoidal waveform but a more complex convolution of a number of waveforms.

An analysis of the active frequencies during different levels of activity is shown in Fig. 4. When asleep lower frequencies predominate as shown in trace a. When awake but relaxed there is a spread of slightly higher frequencies as shown in trace b and the spread of frequencies is higher again when alert as in trace c. The inventors have  
5 recognised that most regeneration of the bodies systems occur during sleep and have therefore found that lower frequencies are most beneficial for promoting repair and recovery with the Magnetic Field Induction Therapy device.

A typical waveform produced by the apparatus of the present invention is shown in Fig. 5. As mentioned above the waveform includes higher harmonic frequencies and  
10 therefore approximates somewhat the waveforms shown in Fig. 3.

Because the waveform is AC there is no time averaged current induced in the treated tissue and therefore the bodies systems are not unbalanced. However, because there are transient currents induced the bodies natural curative mechanisms are enhanced.

The inventors have found through experimentation that the method and apparatus  
15 herein disclosed are useful for temporary relief of pain, arthritis, rheumatism and back ache, for alleviating circulatory and respiratory problems, for reducing inflammation and for treating tendonitis and sports injuries. In particular, they have found that at frequencies between 0.5Hz and 9Hz there is a mild constrictive effect in blood flow which can be important for the treatment of acute stages of injury to  
20 reduce swelling, infection and inflammation. At frequencies between 12Hz and 18Hz the major blood vessels and capillaries are dilated, allowing increased blood flow which is necessary for the secondary stages of healing.

The purpose of this specification has been to describe the invention without limiting the invention to any specific embodiment. Those skilled in the relevant art will be  
25 able to conceive of variations to the specific embodiments which will nonetheless fall within the scope of the spirit of the invention.

**CLAIMS**

1. An apparatus for therapeutic treatment comprising:  
a generator unit adapted to provide alternating current;  
a control means in electrical connection with said generator unit and adapted to  
5 receive as input alternating current from the generator unit and to provide electrical  
signals as output;  
said electrical signals being multi-rhythmic pulsed alternating signals at a frequency in  
the range 0.5Hz to 25Hz;  
and one or more applicator coils in electrical connection with said control means and  
10 adapted to convert the electrical signals to magnetic fields.
2. The apparatus of claim 1 wherein the generator unit includes a step-down  
transformer adapted to convert a primary alternating current voltage source to a  
secondary alternating current voltage source wherein the secondary alternating  
current voltage source has a voltage in the range of 15 volts to 50 volts.
- 15 3. The apparatus of claim 2 wherein the secondary alternating current voltage source  
has a voltage of 18 volts.
4. The apparatus of claim 1 wherein the generator unit includes a step-up  
transformer and DC to AC inverter circuit adapted in combination to convert a direct  
current voltage source to an alternating current voltage source with a voltage in the  
20 range of 15 volts to 50 volts and a frequency of either 50Hz or 60Hz.
5. The apparatus of claim 4 wherein the alternating current voltage source has a  
voltage of 18 volts and a frequency of 50Hz.
6. The apparatus of claim 1 wherein the control means comprises a microprocessor, a  
triac, resistors and capacitors adapted in combination to convert alternating current to  
25 multi-rhythmic pulsed alternating electrical signals.

7. The apparatus of claim 1 further comprising display means adapted to display operating parameters of the apparatus.
8. The apparatus of claim 1 wherein the applicator coils are of wire-wound construction.
- 5 9. An apparatus for therapeutic treatment as herein described with reference to the attached figures.
10. A method of therapeutic treatment including the steps of:  
locating one or more applicator coils adjacent an area to be treated;  
applying electrical signals having frequency, amplitude and pulse characteristics to  
10 said applicator coils so as to produce multi-rhythmic, pulsed, alternating magnetic fields in the vicinity of the coils; and  
adjusting the frequency, amplitude and pulse characteristics so as to produce a pulsating magnetic field having therapeutic effect in the said area to be treated.
11. The method of claim 10 wherein the step of applying electrical signals  
15 includes applying signals with a frequency of 0.5Hz for a time period between zero minutes and thirty minutes.
12. The method of claim 10 wherein the step of applying electrical signals includes applying a sequence of signals, said sequence comprising applying signals having a 2Hz frequency for 30 seconds followed by signals having a 4Hz frequency for  
20 60 seconds followed by having a 8Hz frequency for 90 seconds followed by having a 12Hz frequency for 120 seconds and repeating said sequence a plurality of times.
13. The method of claim 12 wherein the sequence is applied four times for a total treatment time of 20 minutes.
14. The method of claim 10 wherein the step of adjusting the frequency,  
25 amplitude and pulse characteristics is done automatically by a microprocessor means.

15. The method of claim 10 wherein the step of applying electrical signals includes repetitively applying at intervals a chosen treatment until manually stopped.
16. A method as herein described with reference to the attached figures.

# Relevant Technical Fields

- (i) UK Cl (Ed.L) A5R (RHFMX,RHXT)  
(ii) Int Cl (Ed.5) A61N (2/02,2/04)

## Databases (see below)

(i) UK Patent Office collections of GB, EP, WO and US patent specifications.

(ii) ONLINE DATABASES: WPI

Search Examiner  
D C BRUNT

Date of completion of Search  
8 NOVEMBER 1993

Documents considered relevant  
following a search in respect of  
Claims :-  
1-9

## Categories of documents

- |  |   |
|--|---|
| <p><b>X:</b> Document indicating lack of novelty or of inventive step.</p> <p><b>Y:</b> Document indicating lack of inventive step if combined with one or more other documents of the same category.</p> <p><b>A:</b> Document indicating technological background and/or state of the art.</p> | <p><b>P:</b> Document published on or after the declared priority date but before the filing date of the present application.</p> <p><b>E:</b> Patent document published on or after, but with priority date earlier than, the filing date of the present application.</p> <p><b>&amp;:</b> Member of the same patent family; corresponding document.</p> |
|--|---|

Category	Identity of document and relevant passages		Relevant to claim(s)
X	GB 2156679 A	(WALPOLE) whole document	1,8
X	GB 2143131 A	(HASHIMOTO) whole document	1,2,3,8
X	GB 1466337	(KRAUS) see page 2 lines 37-64	1,8
X	EP 0459402 A2	(KRAUS) see column 1 line 50 - column 2 line 23	1,8
X	EP 0048451 A1	(DROLET) see page 14 lines 7-19	1,8
X	WO 91/06341 A1	(ANNINOS) see page 1 lines 5-17	1,8
X	WO 89/05673 A1	(ELECTROMAGNETIC THERAPIES) see page 2 lines 9-20 and page 3 lines 1-15	1,8
X	US 5085626	(FREY) see column 3 line 14 - column 4 line 63	1,2,3,7,8
X	US 4993413	(MCLEOD) see column 4 line 60 - column 5 line 18	1,8

Databases: The UK Patent Office database comprises classified collections of GB, EP, WO and US patent specifications as outlined periodically in the Official Journal (Patents). The on-line databases considered for search are also listed periodically in the Official Journal (Patents).

This Page Blank (uspto)